


















Budynek socjalny - nowoprojektowany

Oznaczenia w projekcie	01	02	03	04	05	06	07	08	09	010	011	012	Db1
Wykaz stolarki okiennej													
Skala 1 : 100													
	Wymiary w świetle So	80	120	180	180	100	100	100	180	220	180	120	150
ościeży	Ho	120	190	120	80	80	150	120	180	150	190	70	230
	Piwnica	2	3	3	3	1	-	-	-	-	4	-	-
Parter	-	-	-	-	-	2	-	-	12	3	-	1	1p
I piętro	-	-	1	-	-	-	1	1	11	3	-	-	-
Ilość sztuk	2	3	4	3	1	2	1	1	23	6	4	1	1p
Uwagi	Otwierane z poziomu posadzki							oddymiające			otwierane z poziomu posadzki	okno podawcze	drzwi balkonowe ewakuacyjne, antypaniczne

W oknach należy zastosować nawiewniki higrosterowalne.
Ilość nawiewników wg projektu instalacji.

Budynek socjalny - istniejący

Oznaczenia w projekcie	013	014	015	016
Wykaz stolarki okiennej				
Skala 1 : 100				
	Wymiary w świetle So	150	90	90
ościeży	Ho	150	150	150
	Piwnica	-	-	2
Parter	2	1	2	-
I piętro	2	1	2	-
Ilość sztuk	4	2	4	2
Uwagi		oddymiające		

W oknach należy zastosować nawiewniki higrosterowalne.
Ilość nawiewników wg projektu instalacji.